

PRODUCT TECHNICAL INFORMATION SHEET

PRODUCT NAME : RED GILT STOCK
REF. CODE : 24320170 (WARESLEY)
DESCRIPTION : RED
MANUFACTURE : SOFT MUD MOULDED STOCK
APPEARANCE : FLAT STOCK
CONFIGURATION : FROGGED
WORK SIZE* : 215 x 102.5 x 65mm

TECHNICAL PROPERTIES BS EN 771-1

COMPRESSIVE STRENGTH : MIN. **21N/mm²**
WATER ABSORPTION : MAX. **24%**
DURABILITY DESIGNATION : **F2**
ACTIVE SOLUBLE SALTS : **S2**
SIZE TOLERANCE * (/ RANGE) : **T2 - R1**
GROSS DENSITY (Tolerance) : **1540Kg/m³ (D1)**
NET DENSITY (Tolerance) : **1840Kg/m³ (D1)**
THERMAL CONDUCTIVITY ($\lambda_{10,dry}$) : P=90% **0.55W/m.K**
INITIAL RATE OF WATER ABS. : MIN. **1.4** MAX. **3.0Kg/m².minute**
BOND STRENGTH (General Mortar) : **0.15N/mm² (fixed value)**
REACTION TO FIRE : Class **A1**
WATER VAPOUR PERMEABILITY (μ): **50/100 (tabulated)**
PACK QUANTITY : **500 no**
PACK SIZE (APPROX. mm) : **1080 x 850 x 860 H**
TYPICAL PACK WEIGHT : **1161 Kg**
PACKAGING : Shrink Wrapping [**YES**] Pallet [**ON REQUEST**]

ISSUE : FEBRUARY 2013