

At the heart of building DECLARATION OF PERFORMANCE

Funton Second Hard Stock A4050A

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.

U for use in Unprotected Masonry

Registered office Ibstock Brick Limited. Leicester Road. Ibstock Leicestershire. LE676HS

Attestation of Conformity System 2+

Notified factory production certification body 1020.CPR/ 10044845 **Lucideon CICS Limited** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

Performance		Harmonised Technical Specification	The performance of the product is in conformity with the declared
Tolerance Range	Tm Rm		performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by: Andy Batterham - Technical & Innovation Director Ibstock Brick Limited
HD units Grou	p 1 Structural		
Mean Normalised Category	12 12.2 Cat I	BS EN771-1:2011/A1:2015	
0.15 S2			
Euro Class A1 21 50/100µ		Commission Decision 2000/605/EC BS EN771-1:2011/A1:2015	
1450 0.72 F2			
	215x1 Tolerance Range Single HD units Grou NF Mean Normalised Category NF 2 50/1 14 0.7	215x102x65 Tolerance Tm Range Rm Single Frog HD units Group 1 Structural NPD NPD Mean 12 Normalised 12.2 Category Cat I NPD 0.15 S2 Euro Class A1 21 50/100µ 1450 0.72	Performance Specification

Data correct since: 31/01/2022

For data prior to this date please contact technical @ibstock.co.uk $\,$

Downloaded: 15/8/2022