

## At the heart of building DECLARATION OF PERFORMANCE

## **Surrey County Red A4132A**

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.

U for use in Unprotected Masonry

Registered office Ibstock Brick Limited. Leicester Road. Ibstock Leicestershire. LE67 6HS

Attestation of Conformity System 2+

Notified factory production certification body 1020.CPR/ 10044845 Lucideon CICS Limited performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

Declared Performance Essential Characteristics	Performance		Harmonised Technical Specification	The performance of the product is in conformity with the declared
Dimensions and tolerance mm	215x1 Tolerance Range	02x65 T2 R1		performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on
Configuration	Vertically Perforated		BS EN771-1:2011/A1:2015	behalf of the manufacturer by:
Group  Flatness of bed faces  Plane parallelism	HD units Group 2 Structural  NPD  NPD			Andy Batterham - Technical & Innovation Director Ibstock Brick
Compressive Strength (tested normal to the bed face of the unit) N/mm²	Mean Normalised Category	40 40.8 Cat I		Limited
Dimensional Stability mm/m  Bond Strength fixed N/mm <sup>2</sup> Active Soluble Salts	0.15 S2			
Reaction to Fire	Euro Class A1		Commission Decision 2000/605/EC	
Water absorption %  Water vapour permeability  Direct airborne sound insulation	12 50/100μ 1450		BS EN771-1:2011/A1:2015	
Thermal resistance W/mk  Durability against freeze thaw	1.15 F2			
Dangerous substances	NPD			

Data correct since: 02/02/2022

For data prior to this date please contact technical@ibstock.co.uk

Downloaded: 29/9/2022