



Product Technical Information Sheet

1 Toddet Teetimeat information offeet	
Wienerberger Code	24320330
Production Plant	Waresley
Manufacture	Extruded/Wirecut
Configuration	Perforated
Colour	Yellow Multi
Appearance	Rolled
Work Size (mm)	215 x 102.5 x 65
Pack Quantity	500 No.
Individual Dry Brick Weight (kg)	1.9



Technical Properties to BS EN 771-1

Size Tolerance (Mean/Range)	⁻ 2/R1
Gross Dry Density (kg/m³/Tolerance) 12	220 (D1)
Compressive Strength (N/mm²) ≥2	25
Thermal Conductivity (W/(m·K)) $\lambda_{10,dry,unit}$ value (EN 1745 tabulated: S1)	P=90% 0.55
Durability Designation F2	2
Water Absorption (%) ≤	:16
Initial Rate of Water Absorption (kg/(m²·min))	/lin. 0.8 Max. 1.8
Active Soluble Salts S2	62
Reaction to Fire C	Class A1

Issue Date: 09/09/2020

Technical data correct at time of issue. Individual dry brick weights can vary and are for guidance only. Any questions regarding this data should be referred to the Wienerberger Technical Department. Due to the limitations of screen and print colour representation of product images it is advised that brick samples are viewed prior to ordering.





1000+ products to choose from



Expert help and advice



Comprehensive Design Services



Technical Support