DECLARATION OF PERFORMANCE

1. Unique identification code of the product type:

Northcot Handmade Autumn Brown Clay Facing Bricks

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

ABH65

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Facing and rendered masonry, load bearing or non load bearing masonry structures including internal linings and partitions for building and civil engineering

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Northcot Brick Limited Station Road Blockley Nr. Moreton-in-Marsh Gloucestershire GL56 9LH

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

6. Declared Performance

| Essential Characteristics | Performance | Harmonised Technical Specification |
|--------------------------------------|---|--|
| Dimensions and Dimensional Tolerance | 215 mm x 102.5 mm x 65 mm Tolerance Class T1 | |
| Configuration | Vertically Perforated Unit as shown in Figure 3c) of EN 771-1. Conforms to the requirements of Group 1 masonry units to EN 1996-1-1 | EN 771-1: 2011 |
| Compressive Strength | 24.5 N/mm ² (tested normal to the bed face of the unit) Cat II | |
| Dimensional Stability | NPD | |
| Bond Strength | Fixed 0.15 N/mm ² | |
| Active Soluble Salts | Class S2 | |
| Reaction to Fire | Class A1 | Commission Decision 2000/605/EC |
| Water Absorption | 14-16% (external elements) | |
| Water Vapour Permeability | 50/100 | |
| Direct Airborne Sound | Gross dry density 1650 Kg/m ³ | EN 771-1: 2011 |
| Insulation | Configuration as above | |
| Thermal Properties | NPD | |
| Durability Against Freeze Thaw | F2 | |
| Dangerous Substances | NPD | |

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Dale Moss, Works Manager

Gloucestershire, 20/03/13

(Signature)