

## At the heart of building DECLARATION OF PERFORMANCE

## Caldew A5089A

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.

U for use in Unprotected Masonry

Registered office lbstock Brick Limited. Leicester Road. lbstock Leicestershire. LE67 6HS

Attestation of Conformity System 4

Notified factory production certification body .CPR/Lucideon CICS Limited performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

| Declared Performance<br>Essential Characteristics   | Performance   |                                 | Harmonised Technical Specification                       | The performance of the product is in conformity with the declared  |
|---|---|---------------------------------|--|--|
| Configuration  Group  Flatness of bed faces  Plane parallelism  | Z15x10 Tolerance Range Vertically F HD units Grou NF NF | T2 R2 Perforated p 2 Structural | BS EN771-1:2011/A1:2015                                  | performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by:  Andy Batterham - Technical & Innovation Director Ibstock Brick Limited |
| Compressive Strength (tested normal to the bed face of the unit) N/mm²  Dimensional Stability mm/m              | Normalised  Category  NF                                | 0<br>Cat II                     |  |  |
| Bond Strength fixed N/mm <sup>2</sup> Active Soluble Salts  | 0.15<br>S2  |                                 |  |  |
| Reaction to Fire  Water absorption%  Water vapour permeability  | Euro Class A1<br>6<br>5/10 mu <i>µ</i>                  |                                 | Commission Decision 2000/605/EC  BS EN771-1:2011/A1:2015 |  |
| Direct airborne sound insulation  Thermal resistance W/mk  Durability against freeze thaw  Dangerous substances | 1300<br>0<br>F2<br>NPD                                  |                                 |  |  |

Data correct since: 02/02/2022

For data prior to this date please contact technical@ibstock.co.uk

Downloaded: 19/8/2022