

At the heart of building DECLARATION OF PERFORMANCE

Hearted Red Rustic A3516A

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.

U for use in Unprotected Masonry

Registered office lbstock Brick Limited. Leicester Road. lbstock Leicestershire. LE67 6HS

Attestation of Conformity System 2+

Notified factory production certification body 1020.CPR/ 10044845 **Lucideon CICS Limited** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

Declared Performance Essential Characteristics	Performance		Harmonised Technical Specification	The performance of the product is in conformity with the declared
Dimensions and tolerance mm	Dimensions and tolerance mm 215x102x65 Tolerance T2 Range R1 Configuration Vertically Perforated		BS EN771-1:2011/A1:2015	performance. This declaration of performance is issued under the sole responsibility of the
Configuration				manufacturer. Signed for and on behalf of the manufacturer by:
Group Flatness of bed faces	HD units Group 2 Structural NPD			Andy Batterham - Technical & Innovation Director Ibstock Brick Limited
Plane parallelism	NPD			
Compressive Strength (tested normal to the bed face of the unit) N/mm ²	Mean	60		AKRAW
	Normalised	61.2		
	Category	Cat I		
Dimensional Stability mm/m	NPD			·
Bond Strength fixed N/mm ²	0.15			
Active Soluble Salts	S2			
Reaction to Fire	Euro Class A1		Commission Decision 2000/605/EC	
Water absorption%	9		BS EN771-1:2011/A1:2015	
Water vapour permeability	50/100μ			
Direct airborne sound insulation	1530			
Thermal resistance W/mk	1.12			
Durability against freeze thaw	F2			
Dangerous substances	NPD			

Data correct since: 02/02/2022
For data prior to this date please contact technical@ibstock.co.uk
Downloaded: 26/8/2022