

## At the heart of building DECLARATION OF PERFORMANCE

## Holbrook Sandfaced Black A4149A

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.

U for use in Unprotected Masonry

Registered office lbstock Brick Limited. Leicester Road. lbstock Leicestershire. LE67 6HS

Attestation of Conformity System 2+

Notified factory production certification body 1020.CPR/ 10044845 **Lucideon CICS Limited** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

Declared Performance Essential Characteristics	Performance		Harmonised Technical Specification	The performance of the product is in conformity with the declared
Dimensions and tolerance mm  Configuration  Group  Flatness of bed faces	215x1 Tolerance Range Vertically F HD units Grou	T2 R1 Perforated p 2 Structural		performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by:  Andy Batterham - Technical & Innovation Director Ibstock Brick Limited
Plane parallelism  Compressive Strength (tested normal to the bed face of the unit) N/mm²	Mean Normalised Category	40 40.8 Cat I	BS EN771-1:2011/A1:2015	
Dimensional Stability mm/m  Bond Strength fixed N/mm <sup>2</sup> Active Soluble Salts	NPD 0.15 S2			
Reaction to Fire  Water absorption%  Water vapour permeability	Euro Class A1 12 50/100µ		Commission Decision 2000/605/EC  BS EN771-1:2011/A1:2015	
Direct airborne sound insulation  Thermal resistance W/mk  Durability against freeze thaw  Dangerous substances	1450 1.15 F2 NPD			

Data correct since: 02/02/2022

For data prior to this date please contact technical@ibstock.co.uk  $\,$ 

Downloaded: 9/9/2022