## **DECLARATION OF PERFORMANCE**

Nº DoP: 624-1-3



Place and date of issue: Hostalets de Pierola, January 22, 2025.

## CERÁMICA PIEROLA, S.L.

CRTA. ESPARRAGUERA A PIERA, KM.10 08781 – HOSTALETS DE PIEROLA (SPAIN)

Edition 1

	00701 - HOSTALLIS DI	LTILKOLA (SI AIIV)
(1) Product ID	oduct ID Facing masonry unit with vertical perforation. Type U.	
(2) Product Identification linked: <b>HEATON DARK RED SMOOTH BRICK 215 x</b>		x102 x 65/73
(3) Intended use(s): Used outside or inside that is intended to have an attractive appearance, on walls, pillars and partitions of unprotected masonry factory.		
(4) Attestation of conformity sy		2+
	tory and of factory production control. ce, assessment and approval of factory production	
(6) Performance declarations:		0099-CPR-A73-0023
Technical Specification	Features	Specification for masonry units
Size Tolerance Mean & Range.	T2 (mean value) / R2 (interval)	masom y umos
Configuration & dimensions	215 65/73	
Average Compression Resistance:	≥40 N/mm² - Category I.	
Dimensional Stability	Moisture movement ≤ 0,5 mm/m	
Bond Strength	Declared value of initial shear strength = $0,15$ N/mm <sup>2</sup> .	EN 771-1:2011 +
Active Soluble Salts contents	Category S2	A1:2015
Reaction to Fire	EUROCLASS A1	A1,2013
Water Absorption	≤ 6 %	
Water vapour permeability (µ) (for units intended to be used in external elements)	Declared value (tabulated water vapour diffusion coefficient: 50/100.	
Direct airborne sound insulation (in end conditions) /Density, Weight and Configuration	Density: 2.200 kg/m <sup>3</sup> Gross dry density: 1.525 kg/m <sup>3</sup> Weight: $(65) \ge 2.100$ g., $(73) \ge 2.350$ g. Configuration: see sketch of the piece.	
Thermal resistance (density and configuration)	Provided value of thermal conductivity ( $\lambda_{10}$ dry unit) = 0,35 W/m.K (tabulated values) Thermal resistance = 0,21 m2 x K/W	
Durability (UNE EN 772-22)	Category F2	
Dangerous substances	NPD	
_	ed product is in conformity with the declared benefits. This d on (EU) N° 305/2011, under the responsibility of the identifie	_
Name and position: Luis Pinardel 1	Nuñez, factory director.	